



## PP Tapes

At EKO-TECH, we use the best raw materials to create PP Solvent packaging tape. Trusted and reliable vendors supply us with the highest quality raw materials. During the production stage, we use PP films with SOLVENT glue with a thickness of 25mic, 28mic and 32mic, which gives the following thicknesses with the glue, 42mic, 44mic, 50mic.

Our area of expertise is the production of 48 mm wide, custom-made PP tape in various lengths. Standard lengths are 54m, 60m, 66m, 132m, 330m and 850m. We can produce any length from 1 m to 1000 m per specific request (the maximum length depends on the outer diameter of the roll).



### Technical data

| Backing thickness | 25mic     | 28mic     | 32mic     |
|-------------------|-----------|-----------|-----------|
| Total thickness   | 42mic     | 44mic     | 50mic     |
| Adhesive          | SOLVENT   | SOLVENT   | SOLVENT   |
| Backing           | PP film   | PP film   | PP film   |
| Adhesive strength | 1.9N / cm | 1.9N / cm | 1.9N / cm |
| Tear resistance   | 38N / cm  | 45N / cm  | 55N / cm  |

For our clients, we can produce a tape from the so-called private label – including sleeves with the customer's logo, cardboard packaging according to customer project and many more.





## PVC Tapes

At EKO-TECH, we use modern machines to make PVC tapes – mostly used in packaging. We can provide any size of the tape – from a width of 5mm to even 1700mm – in any configuration width – length.

The biggest benefit of PVC tapes over conventional PP tapes is unquestionably their better tearing resistance.

In addition, the PVC packaging tape offers properties like restricted stretchability and moisture resistance.

The PVC tape may also be torn by hand, which makes it easier to use.

It makes it possible to manufacture PVC tape under the so-called private label option.



### Technical data

|                          |                     |
|--------------------------|---------------------|
| <b>Backing thickness</b> | <b>32mic</b>        |
| <b>Total thickness</b>   | 50mic               |
| <b>Adhesive</b>          | SOLVENT             |
| <b>Backing</b>           | PVC film            |
| <b>Adhesive strength</b> | 2.4N / cm           |
| <b>Tear resistance</b>   | 47N / cm            |
| <b>Colour</b>            | Transparent / Brown |

