

19801

An economy-grade, light-duty, water-activated carton sealing tape made from natural kraft paper. It uses a starch-based adhesive and is reinforced with fiberglass in the machine direction and polyester in the cross direction to enhance durability.



TECHNICAL PARAMETERS

Color	Brown
Total Thickness	0.14 mm
Composite adhesive	Polymeric copolymer High Melt Adhesive
Water-Activated adhesive	Synthetic modified Starch
Top Ply weight	40 g/m ²
Bottom Ply weight	40 g/m ²
MD Reinforcement	70mm - 110 - (1-1-1-1) - Fiberglass
CD Reinforcement	(1-1-1) Fiberglass, 1" spacing, at 45° angle
MD Tensile strength	>255N / 25mm
CD Tensile strength	>100N / 25mm
Water temperature	Recommended >40°C

APPLICATION:

Designed for two-strip sealing of cartons on the top and bottom. Ideal for use on recycled cartons and non-unitized loads. Suitable for cartons with an average weight of up to 9 kg.

THE PRODUCT COMPLIES WITH EU STANDARDS 2002/95/EG (ROHS) AND 2006/122/EG (PFOS) AND DOES NOT CONTAIN ANY VDA-LISTED SUBSTANCES



All the information given in the above specification was developed under the QMS quality system. They contain product and application information, but do not constitute an assurance of properties. The above information does not relieve you of the obligation to conduct a test under the conditions of application at your company. The product exhibits property tolerances due to the manufacturing process. The values given are an averaging of test results. Assurance of properties in the legal sense is not related to the above data. Technical changes reserved.

The quoted adhesive strength refers to laboratory tests according to specific test standards. In no way does it imply a guarantee of any parameter with respect to other materials and bonding conditions than those specified in the test standard. In addition, due to tolerances occurring in the manufacturing process, the actual adhesive strength of the product may show some deviation from the values stated in the technical documentation.

