

tesa® 4423

Product Information

Paper Stencil Masking Tape for Short-term Sandblasting Applications

Product Description

tesa® 4423 is a special flatback paper masking tape with a strong natural rubber adhesive. The resistant paper backing makes the tape especially suitable as a stencil material or masking tape for spray painting applications and sandblasting glass, mirrors, and stone with the durability of <6 sec./4 bar. tesa® 4423 features excellent adhesive properties on different substrates, good plottability, great paint anchorage, hand tearability and resistance to temperatures of up to 60°C.

<span style="color: rgb(51, 51, 51)

Product Features

- Durability during sandblasting applications 6 sec./4 bar
- Flatback paper backing with goodplottability, paint anchorage, hand tearability and resistance to temperatures up to 60°C
- Good adhesion to various surfaces, clean removal

Application Fields

- tesa® 4423 is suitable as stencil material or masking tape for spray painting applications and sandblasting glass, mirrors, and stone with the durability of <6 sec./4 bar

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | flat paper | • Total thickness | 145 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 5 % | • Hand tearability | very good |
| • Tensile strength | 57 N/cm | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 4.5 N/cm |
|---------|----------|



tesa® 4423

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04423>