

tesa® 60999 PV4



Product Information

Product Description

tesa® 4173 PV2 is resistant to temperatures of up to 105°C for 3000 hours, and is class B flame-resistant. The bundling tape is resistant to abrasion and features class A noise damping.

Product Features

- Excellent wetting property on different kinds of foam, felt material
- Very good converting properties

Application Fields

- Lamination of foam and felt

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|-------------|
| • Backing | non-woven | • Total thickness | 100 µm |
| • Type of adhesive | tackified acrylic | • Color | translucent |
| • Type of liner | PE-coated paper | • Color of liner | white |

Properties/Performance Values

- | | |
|--------|-----------|
| • Tack | very good |
|--------|-----------|

Adhesion to Values

- | | |
|-------------------|----------|
| • Steel (initial) | 6.5 N/cm |
|-------------------|----------|

tesa[®] 60999 PV4

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60999>